

## **RADWIN 2000 C-Plus Series**

### Point-to-Point Radio - Data Sheet

RW-2030-4100



#### **Product Description**

RW-2030-4100 is a carrier-class radio that supports 3.5 GHz and complies with FCC/IC, Universal & IC regulations and factory default: 3.5 GHz FCC/IC.

RW-2030-4100 belongs to the RADWIN 2000 C-Plus Series, delivering 250 Mbps throughput.

The radio comes with an Integrated antenna.

#### **Product Highlights**

- 250 Mbps Ethernet net throughput
- Long range – Up to 40 km / 25 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site TDD synchronization to maximize network capacity
- Configurable asymmetric throughput
- Advanced OFDM & MIMO technologies for operation in nLOS/NLOS and dense radio environments

## Product Specifications:

CONFIGURATION					
Architecture	Outdoor Unit with an Integrated antenna				
PoE to ODU Interface	Outdoor CAT-5e; Maximum cable length: 100m for 10/100BaseT and 75m for 1000BaseT				
RADIO					
Max Capacity	250 Mbps net aggregate throughput				
Range	Up to 40 km / 25 miles				
Channel Bandwidth	Configurable: 5, 10, 20, 40 MHz (for the default band)				
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)				
Adaptive Modulation & Coding	Supported				
Automatic Channel Selection	Supported upon power up				
DFS	Not Supported (for the default band)				
Diversity	Supported				
Spectrum Viewer	Supported				
Max Tx Power	25 dBm				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6				
Encryption	AES 128; FIPS 197; AES 256 optional (via Software License Key)				
Support Indoor units	RADWIN PoE devices (RW-9921-101X)				
Bandwidth Allocation	Configurable: Symmetric or Asymmetric				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
TDD Intra Site Synchronization	Supported				
TDD Inter Site Synchronization	Supported through common GPS receiver per site				
SUPPORTED BANDS					
Band	Channel BW 5MHz	Channel BW 10MHz	Channel BW 20MHz	Channel BW 40MHz	Radio Compliance
3.6 GHz FCC/IC (default)	3.6505-3.6995	3.650-3.700	3.650-3.700	3.650-3.700	FCC 47CFR Part 90 subpart Z; IC RSS-197
3.5 GHz Universal	3.2975-3.8025	3.295-3.805	3.290-3.810	3.280-3.820	Universal
3.5 GHz IC	3.4755-3.6495	3.473-3.652	3.468-3.657	3.458-3.667	IC RSS-192
MECHANICAL					
ODU Dimensions	37(w) x 37(h) x 11(d) cm				
ODU Weight	3.6 kg / 7.94 lbs				
POWER					
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	<20W				
ENVIRONMENTAL					
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1m)				
SAFETY					
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
EMC					
FCC	47 CFR Class B, Part15, Subpart B				
CAN/CSA-CEI/IEC	CISPR 22-04 Class B				
AS/NZS	CISPR 22-2004 Class B				

### Ordering Info

**Part Number:** RW-2030-4100

**Description:** RADWIN 2000 C-Plus ODU, with an Integrated antenna, supporting multi frequency bands at 3.x GHz, factory default 3.6 GHz FCC/IC.